



## STEAM STERILIZER

Automatic Sterilization

8 Sterilization Programs

1 User Defined Program

B & D/HELIX/VACUUM Testing Programs

Cleaning Program

Prevent Infection. Create Safety



Touch key-press brings comfortable user experience

Printer cover



Built-in Printer

USB output

## The Premium

Fully Automatic  
 8 Preset Sterilization Programs  
 Ster. temp: 105-134°C  
 Ster. Time: 4-60 min  
 Dry Time: 1-25 min  
 Vacuum Times: 1-10 times  
 B&D/HELIX/VACUUM Testing  
 Cleaning Program  
 Printer & USB Output Available  
 Big Stainless Steel Water Tanks  
 High-quality Bacterial Filter  
 User Password

### FTZ-23L-E

Capacity	23L
Chamber Size	φ 25*45cm
Display	LCD
Lock	Electrical+Mechanical
Product Size	65*50*43cm
G.W./N.W.	63/55KGS
Power	220V/50HZ 2.4KW
Output	USB+Printer

### FTZ-18L-E

Capacity	18L
Chamber Size	φ 25*35cm
Display	LCD
Lock	Electrical+Mechanical
Product Size	61*50*43cm
G.W./N.W.	61/53KGS
Power	220V/50HZ 2.4KW
Output	USB+Printer

Program	121°C Solid	121°C Hollow	121°C Porous	134°C Solid	134°C Hollow	134°C Porous	Cotton	Prion	User-defined	BD/He-lix Test	Vacu-um Test	Clean
Vacuum time	1	3	3	1	3	3	3	3	User-defined	3	1	3
Temperature (C°)	121	121	121	134	134	134	134	134	User-defined	134	/	105
Pressure (KPA)	110	110	110	210	210	210	210	210	User-defined	210	-80	20
Time (Min)	20	20	20	4	4	4	4	19	User-defined	3.5	15	5